

I-QLUE CA10 Instant Adhesive

Revision: 04.08.2025

Product code: CA10

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

CA10 Instant Adhesive

UFI: VG2X-701F-X00Y-A5P7

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Adhesives and sealants

1.3. Details of the supplier of the safety data sheet

Company name: I-Qlue B.V.
Street: Leidsevaartweg 99-8.02
Place: NL-2106 AS Heemstede
Telephone: +31 6 53265318
E-mail: info@i-qlue.com
Contact person: Max Vuylsteke
E-mail: max@i-qlue.com
Internet: www.i-qlue.com

1.4. Emergency telephone number:

+31 (0)88 755 8000

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Skin Irrit. 2; H315
Eye Irrit. 2; H319
STOT SE 3; H335

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

ethyl 2-cyanoacrylate

Signal word: Warning

Pictograms:



Hazard statements

H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P280 Wear protective gloves/protective clothing and eye protection/face protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 If eye irritation persists: Get medical advice/attention.

I-QLUE CA10 Instant Adhesive

Revision: 04.08.2025

Product code: CA10

Page 2 of 12

P405 Store locked up.
 P501 Dispose of contents/container to an appropriate recycling or disposal facility.

Special labelling of certain mixtures

EUH202 Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.
 People who suffer from skin sensitization problems, asthma, allergies, chronic or recurring respiratory illnesses should not be deployed in any process using this mixture.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
7085-85-0	ethyl 2-cyanoacrylate			80 - < 100 %
	230-391-5	607-236-00-9	01-2119527766-29	
	Skin Irrit. 2, Eye Irrit. 2, STOT SE 3; H315 H319 H335			
123-31-9	1,4-dihydroxybenzene; hydroquinone; quinol			< 0.1 %
	204-617-8	604-005-00-4	01-2119524016-51	
	Carc. 2, Muta. 2, Acute Tox. 4, Eye Dam. 1, Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 1; H351 H341 H302 H318 H317 H400 H410			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
7085-85-0	230-391-5	ethyl 2-cyanoacrylate	80 - < 100 %
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg STOT SE 3; H335: >= 10 - 100		
123-31-9	204-617-8	1,4-dihydroxybenzene; hydroquinone; quinol	< 0.1 %
	oral: LD50 = 302 mg/kg Aquatic Acute 1; H400: M=10 Aquatic Chronic 1; H410: M=1		

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice. Take off immediately all contaminated clothing and wash it before reuse.

After inhalation

Remove casualty to fresh air and keep warm and at rest. If unconscious but breathing normally, place in recovery position and seek medical advice. If experiencing respiratory symptoms: Call a doctor.

After contact with skin

Take off contaminated clothing and wash it before reuse. Gently wash with plenty of soap and water. In case of skin reactions, consult a physician. Do not peel solidified product off the skin. Do not use force or solvents to remove product incrustations from affected skin areas.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids

I-QLUE CA10 Instant Adhesive

Revision: 04.08.2025

Product code: CA10

Page 3 of 12

apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing. Protect uninjured eye.

After ingestion

Rinse mouth thoroughly with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person or a person with cramps. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam, Carbon dioxide (CO₂), Dry extinguishing powder
Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Pyrolysis products, toxic (Carbon monoxide, Carbon dioxide (CO₂))

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Full protection suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes.

For non-emergency personnel

Provide adequate ventilation. Use personal protection equipment.

For emergency responders

Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment.

6.3. Methods and material for containment and cleaning up

For containment

Stop leak if safe to do so. Cover drains.

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Other information

Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

I-QLUE CA10 Instant Adhesive

Revision: 04.08.2025

Product code: CA10

Page 4 of 12

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

Advice on protection against fire and explosion

Usual measures for fire prevention.

Advice on general occupational hygiene

Take off contaminated clothing. Wash hands before breaks and after work. When using do not eat, drink, smoke, sniff.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Keep away from: Food and feedingstuffs
Protect from direct sunlight.
Do not store together with: Oxidizing agent

Further information on storage conditions

Store in a cool dry place. storage temperature: approx. 2 - 8 °C

7.3. Specific end use(s)

Adhesives and sealants

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

I-QLUE CA10 Instant Adhesive

Revision: 04.08.2025

Product code: CA10

Page 5 of 12

DNEL/DMEL values

CAS No	Name of agent		
DNEL type	Exposure route	Effect	Value
7085-85-0	ethyl 2-cyanoacrylate		
Consumer DNEL, acute	inhalation	local	9,25 mg/m3
Worker DNEL, acute	inhalation	local	9,25 mg/m3
Consumer DNEL, acute	inhalation	systemic	9,25 mg/m3
Worker DNEL, acute	inhalation	systemic	9,25 mg/m3
Consumer DNEL, long-term	inhalation	local	9,25 mg/m3
Worker DNEL, long-term	inhalation	local	9,25 mg/m3
Consumer DNEL, long-term	inhalation	systemic	9,25 mg/m3
Worker DNEL, long-term	inhalation	systemic	9,25 mg/m3
123-31-9	1,4-dihydroxybenzene; hydroquinone; quinol		
Worker DNEL, long-term	dermal	systemic	3,33 mg/kg bw/day
Worker DNEL, long-term	inhalation	systemic	2,1 mg/m3
Consumer DNEL, long-term	oral	systemic	0,6 mg/kg bw/day
Consumer DNEL, long-term	dermal	systemic	1,66 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	1,05 mg/m3

PNEC values

CAS No	Name of agent	
Environmental compartment	Value	
123-31-9	1,4-dihydroxybenzene; hydroquinone; quinol	
Freshwater	0,00057 mg/l	
Marine water	0,000057 mg/l	
Freshwater sediment	0,0049 mg/kg	
Marine sediment	0,00049 mg/kg	
Micro-organisms in sewage treatment plants (STP)	0,71 mg/l	
Soil	0,00064 mg/kg	

Additional advice on limit values

To date, no national critical limit values exist.

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection. (EN 166)

Hand protection

Wear suitable gloves. (EN ISO 374)

I-QLUE CA10 Instant Adhesive

Revision: 04.08.2025

Product code: CA10

Page 6 of 12

By long-term hand contact
 Suitable material: Butyl caoutchouc (butyl rubber)
 Thickness of the glove material: > 0,4mm
 Permeation time (maximum wear duration): > 480 min.

By short-term hand contact
 Suitable material: Butyl caoutchouc (butyl rubber)
 Thickness of the glove material: > 0,4mm
 Permeation time (maximum wear duration): > 120 min.

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. (EN 14387) Filter type: A

Thermal hazards

No information available.

Environmental exposure controls

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	black	
Odour:	stinging	
Odour threshold:	not determined	
Melting point/freezing point:		not determined
Boiling point or initial boiling point and boiling range:		96 - 100 °C
Flammability:		Non-flammable.
Lower explosion limits:		not determined
Upper explosion limits:		not determined
Flash point:		85 °C
Auto-ignition temperature:		not determined
Decomposition temperature:		not determined
pH-Value:		not determined
Viscosity / kinematic:		not determined
Water solubility:		Reaction with: Water
Solubility in other solvents		
not determined		
Partition coefficient n-octanol/water:		not determined
Vapour pressure:		< 0,008 hPa
(at 25 °C)		
Density:		1,06 g/cm ³
Relative vapour density:		not determined
Particle characteristics:		not determined

I-QLUE CA10 Instant Adhesive

Revision: 04.08.2025

Product code: CA10

Page 7 of 12

9.2. Other information

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Reaction with: Humidity (Air)

10.4. Conditions to avoid

Protect against: Heat, Frost

10.5. Incompatible materials

Oxidising agent, strong, Water, Amines, Alcohols, Alkali (lye)

10.6. Hazardous decomposition products

 In case of fire may be liberated: Pyrolysis products, toxic (Carbon monoxide Carbon dioxide (CO₂))

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
7085-85-0	ethyl 2-cyanoacrylate				
	oral	LD50 > 5000 mg/kg	Rat	Manufacturer	OECD 401
	dermal	LD50 > 2000 mg/kg	Rabbit	Manufacturer	OECD 402
123-31-9	1,4-dihydroxybenzene; hydroquinone; quinol				
	oral	LD50 302 mg/kg	Rat	IUCLID	

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (ethyl 2-cyanoacrylate)

I-QLUE CA10 Instant Adhesive

Revision: 04.08.2025

Product code: CA10

Page 8 of 12

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

oral, dermal, inhalative, Eye contact

11.2. Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Other information

Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

BCF

CAS No	Chemical name	BCF	Species	Source
7085-85-0	ethyl 2-cyanoacrylate	0,776		

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

I-QLUE CA10 Instant Adhesive

Revision: 04.08.2025

Product code: CA10

Page 9 of 12

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.
14.4. Packing group: No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)


14.1. UN number or ID number: No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.
14.4. Packing group: No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.
14.4. Packing group: No dangerous good in sense of this transport regulation.
 Segregation group: 6 - cyanides

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 3334
14.2. UN proper shipping name: AVIATION REGULATED LIQUID, N.O.S. (METHYLCYANACRYLATE) [only for more than 0,5l]
14.3. Transport hazard class(es): 9
14.4. Packing group: III
 Hazard label: 9



Special Provisions: A27
 Limited quantity Passenger: 30 kg G
 Passenger LQ: Y964
 Excepted quantity: E1
 IATA-packing instructions - Passenger: 964
 IATA-max. quantity - Passenger: 450 L
 IATA-packing instructions - Cargo: 964
 IATA-max. quantity - Cargo: 450 L

Other applicable information (air transport)

Primary packs containing less than 500ml are unregulated by this mode of transport and may be shipped unrestricted.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

I-QLUE CA10 Instant Adhesive

Revision: 04.08.2025

Product code: CA10

Page 10 of 12

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

Directive 2010/75/EU on industrial emissions: < 3 %

Information according to Directive 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

Additional information

Observe in addition any national regulations!

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

I-QLUE CA10 Instant Adhesive

Revision: 04.08.2025

Product code: CA10

Page 11 of 12

Abbreviations and acronyms

Acute Tox. 4: Acute toxicity, hazard category 4
Skin Irrit. 2: Skin irritation, hazard category 2
Eye Dam. 1: Serious eye damage, hazard category 1
Eye Irrit. 2: Eye irritation, hazard category 2
Skin Sens. 1: Skin sensitisation, hazard category 1
Muta. 2: Germ cell mutagenicity, hazard category 2
Carc. 2: Carcinogenicity, hazard category 2
STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3
Aquatic Acute 1: Hazardous to the aquatic environment, hazard category: Acute 1
Aquatic Chronic 1: Hazardous to the aquatic environment, long-term hazard category: Chronic 1
CLP: Classification, Labelling and Packaging
REACH: Registration, Evaluation and Authorization of Chemicals
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
UN: United Nations
EG/EWG: Europäische Gemeinschaft/Europäische Wirtschaftsgemeinschaft
EU: Europäische Union
CAS: Chemical Abstracts Service
M-Factor: Multiplication Factor
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration
ATE: Acute Toxicity Estimate
LC50: Lethal Concentration, 50%
LD50: Lethal Dose, 50%
LL50: Lethal Loading, 50%
EL50: Effect Loading, 50%
EC50: Effective Concentration 50%
ErC50: Effective Concentration 50%, growth rate
NOEC: No Observed Effect Concentration
BCF: Bio-Concentration Factor
PBT: Persistent, Bioaccumulative, Toxic
vPvB: very Persistent, very Bioaccumulative
ADR: Accord européen sur le transport des marchandises Dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
RID: Regulations concerning the International carriage of Dangerous goods by rail
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
(Accord européen relatif au transport international des marchandises Dangereuses par voies de Navigation
intérieures)
IMDG: International Maritime Code for Dangerous Goods
EmS: Emergency Schedules
MFAG: Medical First Aid Guide
IATA: International Air Transport Association
ICAO: International Civil Aviation Organization
TI: Technical Instructions
DGR: Dangerous Goods Regulations
MARPOL: International Convention for the Prevention of Marine Pollution from Ships
IBC: Intermediate Bulk Container
VOC: Volatile Organic Compounds
IE: Industrial Emissions
SVHC: Substance of Very High Concern

Key literature references and sources for data

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety

I-QLUE CA10 Instant Adhesive

Revision: 04.08.2025

Product code: CA10

Page 12 of 12

assessment, chapter R.20 (Table of terms and abbreviations). (v.1.2, 2013)

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H335	Calculation method

Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH202	Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)